

# Product Safety Data Sheet

**XEROX**

**Product:** WorkCentre Pro 412  
FaxCentre F12

**PSDS No.:** 0877  
**ISSUE DATE:** 09/21/01  
**REV. DATE:** 11/01/02

## Section I - Product Identification

**Manufacturer's Name**  
Xerox Corporation

**Emergency No. EH&S Inquiries**  
(585) 422-2177 (800) 828-6571

**Manufacturer's Address**  
Rochester, N.Y.

**Product Designation**  
WorkCentre Pro 412  
FaxCentre F12

**Product Identifier: NA**

## Section II - Electrical Information

<b>Line Voltage</b> (Volts)	<b>Line Current</b> (Amps)	<b>Freq.</b> (Hertz)
100 - 127	4.0	50-60

**Branch Cir. Protection**  
(Amps)  
15

**Line Cord/Plug Specification**  
Equipped with Appliance coupler  
Detachable Cord, Two wire + Ground  
NEMA 5-15P/ -20P

**Power Consumption(Watts)\***

Running: 350  
Standby: 85  
Power Saver: 19

**Agency Approval**  
**UL** File Number E149091  
**cUL** File Number E149091

## Section III - Supplies

	<b>Xerox Part No.</b>	<b>Material Safety Data Sheet</b>
CRU Black	106R584	A28
Drum	113R506	A28

## Section IV - Environmental Information

<b>Product Size</b> (MM)	<b>Heat Emission*</b> (BTU/HR)
D: 429	Running: 1,050
W: 560	Standby: 255
H: 456	Power Saver: 65

**Environmental Limitations**

	<u>Min</u>	<u>Max</u>
Humidity(%)	20	85
Ambient Temp (C)	10	32

**Floor Space Requirements**  
(MM)  
N/A - Desktop unit

**Weight**  
(K Grams.)  
IOT 23

\* Based on a five minute average

\*\* MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2) )

**Section V - Emission/Exposure Information\***

**Light Source**

Light Emitting Diode Display.  
Copy lamp is rare gas Fluorescent:  
The copy lamp is safe for direct viewing  
but to avoid after-glow discomfort this  
should be avoided.  
Class 1 Laser Product

**Accession Number**

9820521-23

**Electromagnetic Emissions**

US FCC: Class A  
Canada DOC: Class A

**Audible Noise**

Run	57dB(A)
Standby	47 dB(A)
Standby (Powersave)	33 dB(A)
Impulse	59 dB(A)

**TLV**

85.0 dB(A)

**Ozone**

The Xerographic process does not produce measurable quantities of ozone.

	ug/min
None detected	ppm (TWA)

**TLV**

0.1 ppm

**Total Dust**

0.0075 mg/m<sup>3</sup>

**TLV**

10 mg/m<sup>3</sup>

**Section VI - Product Recycling and Disposal**

This product may contain lead and other materials whose disposal may be regulated due to environmental considerations. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: [www.eiae.org](http://www.eiae.org). For information on Xerox's worldwide equipment return and recycling programs, visit [www.xerox.com](http://www.xerox.com) (refer to "About Xerox" section).

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time-Weighted Average) for a normal eight-hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.